

DESCRIPTION

ME-W8306 is a self-adhesive fiberglass reinforcing mesh tape with a strong adhesive. It is primarily used by stucco contractors to reinforce architectural foam shapes and trim profiles in outdoor stucco construction. The mesh helps anchor the stucco to the profiles and molded shapes during the stucco application process. This product can also be used by general contractors to reinforce drywall joint compounds (pulling drywall joints). ME-W8306 is designed to be strong yet flexible in order to adhere to contoured surfaces with ease.

APPLICATIONS

- Use to reinforce architectural foam shapes and trim profiles
- Use to reinforce drywall joint compound
- Use to hide joints, cracks and holes permanently in drywall and stucco repair

FEATURES & BENEFITS

- Contours well around shapes for fast and easy application
- Is tear, shrink and bubble proof
- Improves the adherence of stucco to trim profiles and foam shapes

SIZES

- 36" x 150'
- Custom slitting upon request (minimum order quantities apply)

COLOR

- Blue and white

PRODUCT CONSTRUCTION

Backing	Woven fiberglass mesh
Adhesive	Polyacrylic ester

TECHNICAL DATA

Total Thickness	7.9 mils
Weight	65 g/m ² ~ (2.2 oz./yd ²)
Adhesion	50*150mm/10g≥15min 50*150mm/70g≥3min
Tensile Strength	MD ≥440 N/50mm~ (50 lbs/in) TD ≥440 N/50mm ~ (50 lbs/in)
Fabric Count	Warp 2.5cm ~ (9 ± 0.5 mesh/in.) Weft 2.5cm ~ (9 ± 0.5 mesh/in.)
Latex (%)	≥ 26
Application Temperature	23°F to 176°F (-5°C to 80°C)
Service Temperature	-22°F to 428°F (-30°C to 220°C)

STORAGE & USAGE CONDITIONS

**Store tape in its original packaging away from direct sunlight and in a cool and dry area.
For optimum performance, tape should be used within 12 months of date of shipment.
Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.**

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOtape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECHOtape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECHOtape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.