



## **RE-K7333**

# **Single Sided Repulpable Tapping Tape**

RE-K7333 is a 3.5 mils single coated repulpable adhesive tape with a Kraft paper carrier that is coated with water soluble, modified acrylic adhesive.

## **Application**

- Recommended for taping or the temporary or permanent butt splices of light weight, uncoated and coated paper

## **Features & Benefits**

- Very high tensile strength
- High heat resistance and adhesion
- Meets TAPPI 213 repulpable standard°

## **Storage & Usage Conditions**

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

## **Sizes**

Please call for sizes and availability

## Technical Data

Carrier	White Siliconized Repulpable Paper
Adhesive	Water Soluble Acrylic
Total Thickness	3.5 mils
Tensile	28.5 lbs/in
Adhesion	35 oz/in
Maximum Operating Temperature	392°F (200°C)
Elongation	5%
Color	White, Blue

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOtape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECHOtape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECHOtape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.